

Blackmagic Duplicator 4K

Now you can immediately sell content at live events the moment they finish! The Blackmagic Duplicator 4K allows you to deliver Ultra HD content to consumers using the latest technology H.265 files recorded onto inexpensive SD cards. You get realtime H.265 encoding and multi rate 12G-SDI connections for recording all SD, HD and Ultra HD formats up to 2160p60, along with 25 built in SD card recorders. That means you can shoot, record, merchandise and deliver content that customers can actually view on their 4K televisions and Windows 10 computers today!

\$1,995

SD Card Support

Class 10 minimum, will support UHS-I and UHS-II cards.

Connections

SDI Video Input 1 x 10 bit SD/HD/UHD auto switching

SDI Video Output Automatically matches the SD/HD/UHD 12G-SDI input.

SDI Audio Input 16 channels embedded. **SDI Audio Output** 16 channels embedded.


Optical Input 1 x 10 bit SD/HD/UHD auto switching.

Optical Output 1 x 10 bit SD/HD/UHD auto switching.

SD Card Interface 25 x SD Card Slots **Device Control** Sony[™] compatible RS422 deck control port x 2. 1 x in plus 1 x out.

Computer Interface 1 x USB 2.0 Mini-port for software updates and Blackmagic Duplicator software control.

Ethernet supports 10/100/1000 BaseT.



Standards

SD Format Support

525i59.94 NTSC, 625i50 PAL

HD Format Support

720p50, 59.94 1080p23.98, 24, 25, 29.97, 30, 59.94, 60 1080PsF23.98, 24 1080i 60

Ultra HD Format Support

2160p23.98, 24, 25, 29.97, 30, 50, 59.94, 60.

SDI Compliance SMPTE 259M, 292M, 296M, 425M

Audio Sampling

Television standard sample rate of 48 kHz and 24 bit uncompressed.

Video Sampling 4:2:2

Codecs

Supports H.265@ 4:2:0 with AAC audio

Software

Software Included Blackmagic Duplicator

Internal Software Upgrade

Firmware built into software driver. Loaded at system start, or via updater software.

Display

1x built in high res LCD 320 x 240 for menu settings, status, format, audio level and total number of SD cards.

Operating Systems



Mac OS X 10.9 Mavericks, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan or later.



Windows 8.1 64-bit or Windows 10 64-bit.

Power Requirements

Power Supply

IEC Connector with fuse. 110v-240v

Physical Specifications



Environmental Specifications

Operating Temperature 5 to 50°C Environment **Relative Humidity** 0% to 90% non-condensing **Power Requirements** 110-240V

Storage Temperature -20°to 50°C (-4° to 113°F)

What's Included

Blackmagic Duplicator 4K Software SD Card

Warranty

12 Month Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2016, all rights reserved. All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

Blackmagic Design Authorized Reseller